



IECEx Certificate of Conformity

INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification Scheme for Explosive Atmospheres

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.:	IECEx CNEX 17.0001X	Issue No: 0	Certificate history: Issue No. 0 (2017-01-22)
Status:	Current	Page 1 of 4	
Date of Issue:	2017-01-22		
Applicant:	CZ Explosion-proof Electric Appliances Co, Ltd No.1 Qixing Rd, Qixing Town, Nanhu District, Jiaxing, Zhejiang China		
Equipment:	LED explosion-proof light fittings model CZ0870d		
Optional accessory:			
Type of Protection:	Ex db, eb, op is, tb		
Marking:	Ex db eb op is IIC T5/T4 Gb Ex tb IIIC T95°C/T130°C Db		

Approved for issue on behalf of the IECEx
Certification Body:

Wu Jianguo

Position:

Certification Officer

Signature:
(for printed version)

Date:

1. This certificate and schedule may only be reproduced in full.
2. This certificate is not transferable and remains the property of the issuing body.
3. The Status and authenticity of this certificate may be verified by visiting the [Official IECEx Website](#).

Certificate issued by:

CNEX-Global B.V.
Utrechtseweg 310,
6812AR, Arnhem
The Netherlands





IECEx Certificate of Conformity

Certificate No: IECEx CNEX 17.0001X Issue No: 0

Date of Issue: 2017-01-22 Page 2 of 4

Manufacturer: **CZ Explosion-proof Electric Appliances Co, Ltd**
No.1 Qixing Rd, Qixing Town, Nanhu District, Jiaxing, Zhejiang
China

Additional Manufacturing location(s):

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended.

STANDARDS:

The electrical apparatus and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards:

IEC 60079-0 : 2011 Edition:6.0	Explosive atmospheres - Part 0: General requirements
IEC 60079-1 : 2014-06 Edition:7.0	Explosive atmospheres - Part 1: Equipment protection by flameproof enclosures "d"
IEC 60079-28 : 2015 Edition:2	Explosive atmospheres - Part 28: Protection of equipment and transmission systems using optical radiation
IEC 60079-31 : 2013 Edition:2	Explosive atmospheres - Part 31: Equipment dust ignition protection by enclosure "t"
IEC 60079-7 : 2015 Edition:5.0	Explosive atmospheres – Part 7: Equipment protection by increased safety "e"

*This Certificate **does not** indicate compliance with electrical safety and performance requirements other than those expressly included in the Standards listed above.*

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in

Test Report:

[NL/CNEX/ExTR17.0001/00](#)

Quality Assessment Report:

[CN/CQM/QAR08.0001/05](#)



IECEx Certificate of Conformity

Certificate No: IECEx CNEX 17.0001X

Issue No: 0

Date of Issue: 2017-01-22

Page 3 of 4

Schedule

EQUIPMENT:

Equipment and systems covered by this certificate are as follows:

The LED explosion-proof light model CZ0870d is made of an aluminum enclosure with a toughened glass window and consists of a light and electronics compartment in type of explosion protection flameproof enclosure 'db' and a terminal enclosure in type of explosion protection increased safety 'eb'. If used in explosive dust environments, the enclosure can be regarded as having the type of explosion protection 'tb'.

See the Annex for further details.

CONDITIONS OF CERTIFICATION: YES as shown below:

The ambient temperature range is limited as follows:

$-20\text{ }^{\circ}\text{C} \leq T_a \leq +40\text{ }^{\circ}\text{C} / +55\text{ }^{\circ}\text{C}$, or

$-40\text{ }^{\circ}\text{C} \leq T_a \leq +40\text{ }^{\circ}\text{C} / +55\text{ }^{\circ}\text{C}$.

Repair of the threaded joints must be made in compliance with the specifications provided by the

manufacturer. Repairs must not be made only on the basis of values specified in table 4 of

EN 60079-1.

The two fasteners screws on the lamp body shall only be replaced with the correct type, provided by the manufacturer. See the Operating Instructions from the manufacturer.



IECEx Certificate of Conformity

Certificate No: IECEx CNEX 17.0001X

Issue No: 0

Date of Issue: 2017-01-22

Page 4 of 4

Additional information:

Additional Information:

The enclosure of the LED explosion-proof light model CZ0870d successfully passed the tests for the Ingress Protection level IP66 to EN 60529.

Annex:

[P150002-CCA Annex 01 to IECEx CoC.pdf](#)



Annex 01 to Certificate IECEx CNEX 17.0001X

Equipment or Protective System: LED Explosion-proof Light Fittings
model CZ0870d/□□-LED □W

Manufacturer: CZ Explosion-proof Electric Appliances Co., Ltd.

Address: No.1 Qixing Rd, Qixing Town, Nanhu District, Jiaxing,
Zhejiang, P.R. China

Nomenclature for CZ 08 70 d / a b – LED cW:

CZ = Manufacturer abbreviation
08 = Year of development
70 = Light fitting specification code
d = Flame proof 'd'
a = Angle of luminous code (105=120°, 108=60°, 110=85°x135°, 112=40°)
b = Mounting arrangements (B=Bracket type lamp, C=Platform type lamp 90°,
D=Platform type lamp 25°, E=Wall type lamp, F=Street lamp)
LED = LED light source
cW = Power (90 W, 120 W or 160 W)

Electrical Data:

Rated voltage : 110~250 Vac
Rated power : 90 W, 120 W, 160 W
Rated frequency : 50/60 Hz

Mounting Instructions:

See the Operating Instructions from the manufacturer.

Installation Instructions:

Only suitable certified increased safe cable glands and stopping plugs are to be used, suitable for the conditions of use, minimum IP66 rated and correctly installed.
See the Operating Instructions from the manufacturer.

Routine tests:

Each flameproof enclosure shall be tested conform EN 60079-1 cl. 16.1, with an overpressure maintained for minimum 10 seconds, as follows:

Ambient temperature range [°C]	Electronics compartment [MPa]	Light source compartment [MPa]
-20 ≤ Ta ≤ +40 / +55	1.14	1.04
-40 ≤ Ta ≤ +40 / +55	1.26	1.46

Each increased safe terminal compartment shall be tested with a dielectric strength test conform EN 60079-7 cl. 7.1, with a voltage of 1500 Vac for minimum 60 seconds.

Descriptive Documents:

Detailed in the Test Report Cover document. (ref. CQST/ExTR1601G001).

Certification Body: CNEX-Global B.V., Utrechtseweg 310, 6812 AR, Arnhem, the Netherlands

This Annex may only be reproduced in its entirety and without any change